

SAFETY DATA SHEET



MSDS NO. ABS FR 984001R

ReStart - ABS FR1

Access Date: 5/14/2020

Page 1

SECTION 1: IDENTIFICATION

Product Identifier: ABS flame retardant

Chemical Formula: Acrylonitrile, Butadiene, Styrene containing a halogenated organic with antimony

General Product Use: May be used to produce molded or extruded articles or as a component of other industrial products.

Manufacturer: Star Plastics, Inc. 326 Jack Burlingame Drive
Millwood, West Virginia 25262, USA
StarPlastics.com
Phone: 304.273.0352 (24 Hours)
Fax: 304.273.0355

Emergency telephone number: 304.273.5326 (24 hours)

SECTION 2: HAZARD(S) IDENTIFICATION

Classifications: Use Appendices to 1910.1200 to determine Hazard Classification.

Pictograms:



Signal Word: Warning

Hazard Statements: Spilled pellets create slipping hazard.

Precautionary Statements: Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation.

Other Hazards not Otherwise Classified: Pellet inhalation unlikely due to physical form.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical/Component Name	CAS Number	Weight %
Acrylonitrile	107-13-1	
Butadiene	106-99-0	
Styrene	100-42-5	
Antimony Oxide	1309-64-4	
<i>for codes containing high black content</i>		
Carbon Black	1333-86-4	
<i>for codes containing high white content</i>		

Titanium Dioxide

13463-67-7

SECTION 4: FIRST-AID MEASURES

Inhalation: Remove to fresh air. Call medical support.

Eye Contact: Flush immediately with large amounts of water for at least 15 minutes. If irritation persists, call medical support.

Skin Contact: For molten plastic skin contact, cool rapidly with water and immediately seek medical attention. Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.

Inhalation: Fume inhalation- Leave contaminated area and breathe fresh air. If coughing, difficult breathing or any other symptoms develop seek medical attention at once, even if symptoms develop at a later time.

Ingestion: Not probable.

Most important symptoms/effects: Coughing, difficult breathing

Indication of immediate medical treatment:

SECTION 5: FIRE-FIGHTING MEASURES

Suitable (and unsuitable) Extinguishing Media: Dry chemical, water spray, carbon dioxide, foam, water fog or spray.

Specific Hazards arising from the chemical: Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide and hydrocarbon fragments.

Special protective equipment and precautions for fire-fighters: Wear NIOSH/MSHA approved SCBA and full protective equipment.

The fuel content and temperatures will require immediate attention and vigorous efforts to bring about control of the fire, and suppression of the fire should begin immediately. The plastic will melt, but it will not be carried on the surface of the water, and water can be freely used to control the fire. Use a water spray to cool fire-exposed containers, and to solidify. Do not release runoff from fire control methods to sewers or waterways.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Pellets: Remove from all floor areas to allow for stable footing

Precautions/protective equipment/emergency procedures: and preventing slips by personnel.

Soil: Collect for re-use or appropriate disposal. Solids can be separated.

Water: Notification of government agency may be appropriate.

Air: Not likely to be released.

Methods/materials for containment & clean-up: Do not release runoff from fire control methods to sewers or waterways.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling: Fumes emitted from hot plastic during conversion may condense on cool overhead metal surfaces/structures.

Secondary operations such as grinding, sanding or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation; employ bonding, grounding, venting and explosion relief provisions in accordance with accepted engineering practices.

Conditions for Safe Storage: Avoid storing containers near foodstuffs due to possibility of odor and taste contamination of food.

Do not store containers near heating devices, hot pipes, etc.

Read and become familiar with all labels and instructions of packaging.

Store in a dry place away from moisture, excessive heat and sources of ignition.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

OSHA PEL/ACGIH/TLV:

	OSHA PEL (TWA)	STEL	Ceiling
Acrylonitrile	2 ppm	10 ppm	
Butadiene	1 ppm	5 ppm	
Styrene	100 ppm		200 ppm
Antimony Oxide <i>for codes containing high black content</i>	0.5 mg/m ³		
Carbon Black	3.5 mg/m ³		

for codes containing
high white content

Titanium Dioxide 15 mg/m³

Appropriate Engineering Controls: Recommended, sufficient ventilation to control fumes.

Individual Protection Measures:

Respiratory Protection: Under conditions of excessive fume concentration, a NIOSH/MSHA approved device with organic vapor acid gas rating or fresh air supply should be used. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Hand Protection: Wear gloves that will prohibit penetration when handling hot plastic.

Eye Protection: ANSI approved safety glasses or chemical workers goggles.

Other Protective Equipment: Ordinary work clothes.

Work Hygienic Practices: Wash hands with soap and water before eating or smoking and at the end of each work day.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid	Explosive Limits:	Unknown
Odor:	Faint	Vapor Pressure:	Negligible
Odor Threshold:	N/A	Vapor Density:	Unknown
pH:	N/A	Relative Density:	Unknown
Freezing/Melting point:	This product does not exhibit a sharp melting point, but softens gradually over a wide temperature range.	Solubility:	Insoluble

Boiling Point/Range:	Unknown	Other Solubility:	Unknown
Flash Point:	Unknown	Partition Coefficient:	Unknown
Evaporation Rate:	N/A	Auto-Ignition Temp:	Unknown
Flammability (solid, gas):	N/A	Decomposition Temp:	Unknown
Viscosity:	N/A	UEL/LEL:	Unknown

SECTION 10: STABILITY AND REACTIVITY

Reactivity:	Not reactive under recommended conditions of handling, storage, processing and use.
Chemical Stability:	Stable under recommended conditions of storage and handling.
Possibility of Hazardous Reactions:	
Conditions to Avoid:	Do not exceed melt temperature recommendations in product literature. In order to avoid autoignition/hazardous decomposition of hot thick masses of plastic, purgings should be collected in small, flat shapes or thin strands to allow for rapid cooling and quench in water.
Incompatible Materials:	
Hazardous Decomposition Products:	Processing fumes evolved at recommended processing conditions contain trace levels of styrene monomer, ammonia, acrylamide, aromatic and aliphatic hydrocarbon fragments, hydrogen bromide and CO.

SECTION 11: TOXICOLOGICAL INFORMATION

	Information on toxicological effects
Routes of Exposure:	Inhalation, skin, ingestion
Eye:	Product may cause irritation or injury due to mechanical action.
Skin Contact:	Pellets not likely to cause skin irritation.
Ingestion:	Not acutely toxic.
Inhalation:	Pellet inhalation unlikely due to physical form.
Symptoms:	
Delayed & Immediate Effects:	Fumes produced during melt process of plastics may produce acute health effects in some individuals, especially irritation of eyes/nose and throat in cases of severe overexposure, nausea and headaches.
Numerical Measures of Toxicity:	

Carcinogenicity: Acrylonitrile: IARC Group 2A, NTP anticipated to be a carcinogen, ACGIH Group A2, OSHA regulates styrene: IARC Group 2B. OSHA, IARC and NTP have listed carbon black as carcinogen. Titanium Dioxide has been identified as a suspected or confirmed human carcinogen. OSHA, IARC and/or NTP have listed heavy metals, present in some colorants as carcinogens. These colorants are essentially bound to the plastic matrix and are unlikely to contribute to workplace exposure under recommended processing conditions.

SECTION 12: ECOLOGICAL INFORMATION (NON-MANDATORY)

Ecotoxicity: N/A
Persistence and degradability: N/A
Bioaccumulation potential: N/A
Mobility in soil: N/A
Other adverse effects: N/A

SECTION 13: DISPOSAL CONSIDERATIONS (NON-MANDATORY)

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging.

Landfill waste plastic if codes permit; incinerate if codes and equipment permit. Incinerating equipment should be capable of handling large volumes of dense, black smoke and withstand effects of acid gases. Pellet materials not considered hazardous waste.

SECTION 14: TRANSPORT INFORMATION (NON-MANDATORY)

UN Number: N/A
UN Proper Shipping Name: N/A
Transport Hazard Class(es): N/A
Packing Group, if applicable: N/A
Environmental hazards (eg, Marine pollutant): N/A
Transport in Bulk (according to Annex II of MARPOL 73/78 and the IBC Code): N/A
Special Precautions which a user needs to be aware of, or needs to comply with, in N/A

**connection with transport of conveyance
either within or outside their premises:**

DOT Transportation Data: 49 CFR 172.101

SECTION 15: REGULATORY INFORMATION (NON-MANDATORY)

Safety, Health and Environmental Regulations specific for the product in question.

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261.??): Not classified

CERCLA Hazardous Substance (40 CFR 302.4) Unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ)

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed

OSHA Specifically Regulated Substance: Not listed.

State Regulations: Not listed

California Proposition 65:



WARNING: This product can expose you to chemicals: Acrylonitrile (CAS# 107-13-1), Butadiene (CAS# 106-99-0), Styrene (CAS# 100-42-5), Tetrabromobisphenol A (CAS# 79-94-7), Antimony Oxide (CAS# 1309-64-4) which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

Listed on the active section of the TSCA Inventory

SECTION 16: OTHER INFORMATION

Prepared By: Star Plastics, Inc

Date of Preparation: 11/19/2013

Revision: 01

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.