



## Component – Plastics

**E205256**

### Star Plastics, LLC

326 Jack Burlingame Dr, Millwood, WV 25262 USA

### Material Designation: ABS3545

Product Description: Acrylonitrile Butadiene Styrene (ABS), Furnished as Pellets

| Color | Min Thk (mm)   | Flame Class | HWI | HAI | RTI Elec | RTI IMP | RTI Str |
|-------|----------------|-------------|-----|-----|----------|---------|---------|
| ALL   | 1.5 – 2.9 ONLY | HB          | -   | -   | 60       | 60      | 60      |

Comparative Tracking Index (CTI): -

Dielectric Strength (kV/mm): -

Dimensional Stability (%): -

High-Voltage Arc Tracking Rate (HVTR): -

Inclined Plane Tracking (IPT): -

 Volume Resistivity (10<sup>9</sup>ohm-cm): -

High Volt, Low Current Arc Resis (D495): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliance, where the acceptability of the combination is determined by UL.

Access Date: 7/9/2025

2013 UL LLC©



## IEC and ISO Test Methods

| Test Name                      | Test Method     | Units             | Thickness Tested (mm) | Value      |
|--------------------------------|-----------------|-------------------|-----------------------|------------|
| Flammability                   | IEC 60695-11-10 | Class (color)     | 1.5 – 2.9 ONLY        | HB75 (ALL) |
| Glow-Wire Flammability (GWFI)  | IEC 60695-2-12  | C                 | -                     | -          |
| Glow-Wire Ignition (GWI)       | IEC 60695-2-13  | C                 | -                     | -          |
| IEC Comparative Tracking Index | IEC 60112       | Volts (max)       | -                     | -          |
| IEC Ball Pressure              | IEC 60695-10-2  | C                 | -                     | -          |
| ISO Heat Deflection (1.80 MPa) | ISO 75-2        | C                 | -                     | -          |
| ISO Tensile Strength           | ISO 527-2       | MPa               | -                     | -          |
| ISO Flexural Strength          | ISO 178         | MPa               | -                     | -          |
| ISO Tensile Impact             | ISO 8256        | kJ/m <sup>2</sup> | -                     | -          |
| ISO Izod Impact                | ISO 180         | kJ/m <sup>2</sup> | -                     | -          |
| ISO Charpy Impact              | ISO 179-2       | kJ/m <sup>2</sup> | -                     | -          |